



AVAILABLE CONNECTION SYSTEMS













TECHNICAL SPECIFICATIONS

External dimensions	292mm x 262 mm
Interaxis	239 mm x 239 mm
Main tube	Round tube Ø 50x2 mm Aluminium EN AW 6082-T6
Diagonal tube	Round tube Ø 20x2 mm Aluminium EN AW 6060-T6
Endplate	Casting Aluminium
Coupling set	Conical spigots, pins and clips (standard) / Bolts (on request)

STANDARD LENGTHS

LENGTH (m)	0.21	0.50	1.00	1.50	2.00	2.50	3.00	3.50	4.00
WEIGHT (kg)	-	4.1	6.1	8.1	10.2	12.2	14.3	16.3	18.3

Loading distribution WITH SPIGOTS	CPL		2PL		3PL		4PL		UDL		
											
Length	↓	↓	↓↓	↓↓	↓	↓↓	↓	↓↓	U.D.L. (kg/m)	Total load weight (kg)	Max central Deflection (cm)
4 m	454	305	710	710	203	609	169	676	227	908	1.8
6 m	293	198	396	396	132	396	110	440	97	582	4.1
8 m	209	144	288	288	96	288	80	320	52	416	7.1
10 m	156	109	218	218	73	219	61	244	31	310	10.9
12 m	119	86	172	172	57	171	48	192	19	228	14.8
14 m	91	68	136	136	45	135	38	152	13	182	20.2
16 m	68	54	108	108	36	108	30	120	9	144	26.3